



GB 2100 - Discharging gravels



GB 2100



GB 2100 - Sweeping

- More versatility: Can be used for material handling and sweeping/collecting.
- Forward : sweeping with raised brush to reduce trash thickness or for loading
Backward : brush down for finishing and collecting
- 5 sweeping widths :
1,20 m - 1,50 m - 1,80 m - 2,10 m or 2,40 m
- Adaptation on telescopic, backhoe loader, loader...
- Longer brush life: brush mechanically adjustable for wear.
- Mixed brush (polypropylene / polyester), Ø 600 mm.
- Extra strength: 16 mm thick cutting blade and bucket with reinforcing counter-fold.
- Emptying of the bucket by breaking it out thanks to the hydraulic cylinder.



Dust collection with the bucket

Technical characteristics

MODELS	GB 1200	GB 1500	GB 1800	GB 2100	GB 2400
Coupling	Loader, Telescopic, Backhoe loader...				
Brush length	1200 mm	1500 mm	1800 mm	2100 mm	2400 mm
Diameter (inner / outer)	178 mm / 600 mm				
Hub	Metal				
Brush fibre type	Mixed (polypropylene/polyester)				
Dimensions (L x W x H)	1,23 x 1,32 x 0,87 m	1,23 x 1,62 x 0,87 m	1,23 x 1,97 x 0,91 m	1,23 x 2,27 x 0,91 m	1,23 x 2,57 x 0,91 m
Weight (1 motor / 2motors)	330 kg	505 kg	555 / 575 kg	605 / 625 kg	655 / 675 kg
Flow 1 hydraulic motor	20 L/min. mini. - 60 L/min. max.				
Flow 2 hydraulic motor	-			61 L/min. mini. - 120 L/min. max	
Pressure	200 bar				
Collecting box emptying	Hydraulic cylinder (dual-acting)				
Real collecting box volume	410 L	510 L	610 L	710 L	810 L

Standard equipment

- Collecting box : 410, 510, 610, 710 and 810 L according to the model.
- Mixed brush (polypropylene / polyester), Ø 600 mm.
- 2 hydraulic hoses with 2 ½" male valve couplings.



With coupling to determine: here for telescopic



Mounting on articulated loader

MODELS	£	Reference
GB 1200 • 1 hydraulic motor for carriers with oil flow < 60 L/min.	4,050	72066J
GB 1500 • 1 hydraulic motor for carriers with oil flow < 60 L/min.	4,420	72070G
GB 1800 • 1 hydraulic motor for carriers with oil flow < 60 L/min. • 2 hydraulic motor for carriers with oil flow > 60 L/min.	4,810 5,915	72071G 72072G
GB 2100 • 1 hydraulic motor for carriers with oil flow < 60 L/min. • 2 hydraulic motor for carriers with oil flow > 60 L/min.	5,270 6,365	72073G 72074G
GB 2400 • 1 hydraulic motor for carriers with oil flow < 60 L/min. • 2 hydraulic motor for carriers with oil flow > 60 L/min.	5,905 6,940	72075G 72076G
LINKAGE > OBLIGATORY TO DETERMINE		
• Backhoe loader, loader, compact loader, skid steer loader, farm loader	545	76037F
• Excavator attachment with 8-hole plate	620	76039F
OPTION		
Kit to hold the brush when emptying – for telescopic type Merlo, Bobcat..	410	72026G
SPARE BRUSH		
Mixed brush ring (polypropylene/polyester) Ø 600 mm, value for 1 m	300	24F006



OPERATION :

- Forward -> collecting
- Backward -> sweeping