



XYLOCRIBLE 2 M



XYLOCRIBLE 4 m + buffering screener



Rabaud
advantages

- 2 models with large sifting areas (L x W) :
2 x 1 m on XYLOCRIBLE 2 M.
4 x 1 m on XYLOCRIBLE 4 M.
- Rolls driven electrically or hydraulically.
- Wood screener loading by bucket or wood processor outcome conveyor.
- Square cam rolls to separate the waste from the logs.
- Underneath waste evacuation.
- Custom configuration.
- Option : 6 cubic meters volume buffering storer through metal laths conveyor.

Technical characteristics

MODELS	XYLOCRIBLE 2M	XYLOCRIBLE 4M
<i>Sifting area (L x W)</i>	2 x 1 m	4 x 1 m
<i>Number of cams</i>	6 square + 1 «round» cam roll	15 square + 1 «round» cam roll
<i>Netting width</i>		48 mm
<i>Disc thickness</i>		12 mm
<i>Rotation speed</i>		58 rpm
<i>Weight</i>	from 1300 kg	From 4000 kg

— Standard equipment —

- Front and side loading hopper on XYLOCRIBLE 4 M.
- Individual and offset lubricating system for chain bearings.
- Progressive start-up motion for electric version.
- Reverse gear on electric versions.



Specific conditions :
Consult us



For more information, contact us



Specific conditions :
Consult us

	£	Reference
MODELS		
XYLOCRIBLE 2 METERS Stationary version - Adjustable unloading height • ET : Electric drive 2.2 kW three-phase	1 14,995	70239A
• ET + RADIO CONTROL : Electric drive 2.2 kW three-phase + radio control	2 16,615	70237A
• PH : Hydraulic drive (25 L/min. oil flow)	3 13,945	70240A
OPTIONS		
Fixed delivery chute (mounted on the screener) : 350 mm length	705	70241A
Adjustable delivery chute (mounted on the screener) : 750 mm length	980	70242A

	£	Reference
MODEL		
BUFFERING UNIT WITH INCLINED LATH CONVEYOR + XYLOCRIBLE 2 METERS + RADIO CONTROL Stationary version - 3.17 m unloading height Electric drive 2.2 kW 3-phase for the screener and 3 kW three-phase + radio control for the storer	4 36,185	70243A
OPTIONS		
Fixed delivery chute (mounted on the screener) : 350 mm length	705	70241A
Adjustable delivery chute (mounted on the screener) : 750 mm length	980	70242A
Inspection hatch for lath inclined conveyor	1,965	70298A

	£	Reference
MODELS		
XYLOCRIBLE 4 METERS • ET : Electric drive 4 kW three-phase	5 29,765	70223A
• ET + RADIO CONTROL : Electric drive 4 kW three-phase + radio control	6 31,405	70224A
• PH : Hydraulic drive (25 L/min. oil flow)	7 25,740	70225A
SET UP TYPE > OBLIGATORY TO DETERMINE		
Stationary version with 1.30 m unloading height from the ground	3,375	70229A
Stationary version with unloading height to define (1.30 m mini.) – Price for 1 m	3,120	DIV702
Rolling version with axle + drawbar with foldable hook – 2.85 m unloading height	4,720	70206A
On rails with 5 m translation	15,910	DIV702
OPTIONS		
Adjustable delivery chute : 800 mm length	1,055	70213A
Adjustable delivery chute : 1450 mm length	1,210	70214A
Discharge conveyor for waste under sifter	Contact us	DIV702
8 m discharge conveyor with hydraulic distributor + hydraulic unit (on PH version)	Contact us	

	£	Reference
MODELS		
BUFFER STORAGE BY STRAIGHT SLATTED BELT + XYLOCRIBLE 4 METERS • ET : 4 kW three-phase electric drive for screening machine and buffer storage unit	8 50,135	70219A
• ET + RADIO CONTROL : Electric drive 4 kW - three-phase for the screener and 3 kW - three-phase for the storer + radio control	9 51,730	70220A
BUFFERING UNIT WITH INCLINED LATH CONVEYOR + XYLOCRIBLE 4 METERS • ET + RADIO CONTROL : Electric drive 4 kW - three-phase for the screener and 3 kW - three-phase for the storer + radio control	10 53,495	70276A
SET UP TYPE > OBLIGATORY		
Stationary version with 1.17 m unloading height – Price for 1 m	2,975	DIV702
OPTIONS		
Adjustable delivery chute : 800 mm length	1,055	70213A
Adjustable delivery chute : 1450 mm length	1,210	70214A
Inspection hatch for lath inclined conveyor	1,965	70298A



