



CLOTURMATIC GRX 4020 + 1 row
barbed wire unwinder



CLOTURMATIC GRX 4020 + 1 row
barbed wire unwinder



CLOTURMATIC GRX 4020 at work



Rabaud advantages

- Unwinds netting rolls wire from 0 up to 2.50 m height (on GRX 8025) and up to 800 mm diameter.
- Barbed wire uncoiled for 1 or 2 rows above the wire netting.
- Hydraulic stretching system for the wire netting.
- Clamp for maintaining tension when fixing or joining rollers.
- Loading platform for putting up the wire netting roll.
- Air nailing pistol (optional)
- Wire netting always clean and put effortlessly, as the unwinding is made in vertical position.
- Many options:
 - 2-way dual acting valve,
 - Air nailing pistol,
 - Air compressor for the nailing pistol,
 - barbed wire unroller (maximum 2).

Technical characteristics

MODELS	GRX 4020	GRX 8025
<i>Wire netting roll diameter</i>	from 0 up to 400 mm	from 0 up to 800 mm
<i>Roll height : without barbed wire</i>	2.00 m max.	2.50 m max
<i>Roll height : with 1 barbed wire strand</i>	1.52 m max	
<i>Roll height : with 2 barbed wire strand</i>	1.37 m max	1.37 m max
<i>Dimensions (L x W x H)</i>	1,83 x 1,90 x 2,27 m	2,21 x 1,96 x 2,81 m
<i>Weight</i>	585 kg	985 kg
<i>Drive</i>	Tractor hydraulic pump with hydraulic hoses or PTO 540 rpm - flow 34 L/min.	
<i>Coupling</i>	Tractor N°2 3-point hitch with removable pins or Hitch for other carriers Tractor from 80 or 100 HP	



Wire + 2 rows barbed wire



CLOTURMATIC GRX 8025

Standard equipment

- Hydraulic drive with tractor pump.
- Hydraulic tightening system with 2 cylinders, 2 hydraulic hoses and 2 ½" male valve couplings.
- Tension clamp system with 2 cylinders, 2 hydraulic hoses and 2 ½" male valve couplings.



CLOTURMATIC GRX with
2 rows barbed wire uncoiler



Air nailing pistol for staples

MODELS		£	Reference
WIRE NETTING UNWINDING MACHINE / KNOTED / MULTITWISTED •CLOTURMATIC GRX 4020 (roll size Ø 400 mm - 2,00 m high)		5,720	77021A
WIRE NETTING UNWINDING MACHINE / KNOTED / MULTITWISTED •CLOTURMATIC GRX 8025 (roll size Ø 800 mm - 2,50 m high)		7,335	77026A
OPTIONS			
2-way dual acting valve		635	77022A
Hydraulic unit	With 2-way dual acting valve	1,535	DIV770
	With 2-way dual acting valve + Air compressor (PTO drive) : Automatic unwinder for 8 m pipe - Tool chest - Pressure regulator and manometer - 50 L air tank + Air nailing pistol for 11 mm width staples (loading of 130 staples)	8,135	70102B
Compressor kit + Air nailing pistol Air compressor (PTO drive) : Automatic unwinder for 8 m pipe - Tool chest Pressure regulator and manometer - 50 L air tank Air nailing pistol : for 11 mm width staples (loading of 130 staples)		6,560	77061A
Staples	Galvanized - width 11 mm - Length 45 mm - Section 1.7 / 1.9 mm - Packed in a box of 8800 staples	310	770017
	Stainless steel - Width 11 mm - Length 45 mm - Section 1.7 / 1.9 mm - Packed in a box of 7500 staples	1,085	770007
Electromechanical time meter (for machine with hydraulic unit)		785	DIV727
Barbed wire uncoiler	1 row - for CLOTURMATIC GRX 4020 (netting 1.52 m high maximum)	1,730	77027A
	2 rows - for CLOTURMATIC GRX 4020 (netting 1.37 m high maximum)	2,680	77028A
	1 row - for CLOTURMATIC GRX 8025 (netting 1.52 m high maximum)	1,730	77051A
	2 rows - for CLOTURMATIC GRX 8025 (netting 1.37 m high maximum)	2,680	77052A
Wire netting winder for GRX 8025 only		2,385	77060A



CLOTURMATIC GRX 4020



CLOTURMATIC GRX 4020