



CLOTURMATIC RXB



CLOTURMATIC RXB



Air nailing pistol for staples

- 4 models for fencing with 2, 3, 4 or 5 rows of barbed wire in 1 pass.
- Unwind and lay barbed wire in coils (max. 500 m).
- Barbed wire rows are all stretched with same tension thanks to pinions and individual disc brakes.
- Perfect lining of the barbed wires against the post thanks to the 1.00 m hydraulic side shift.
- Slope correctors +/- 30° for setting up the wire parallel to the posts.
- Adjustable row spacing from 145 to 300 mm.
- Air nailing pistol with stainless steel or galvanized staples (in option).
- Loading platform for barbed wire coils.
- Sign lighting kit.



Technical characteristics

| MODELS | 2 RXB | 3 RXB | 4 RXB | 5 RXB |
|---|---|---------|---------|---------|
| <i>Number of barbed wire rows</i> | 2 | 3 | 4 | 5 |
| <i>Inner coil diameter</i> | 95 mm minimum | | | |
| <i>Hydraulic offset</i> | 1,00 m | | | |
| <i>Dimensions without uncoilers (L x W x H)</i> | 1,93 x 2,43 x 1,50 m | | | |
| <i>Dimensions with uncoilers (L x W x H)</i> | 1,93 x 2,43 x 2,38 m | | | |
| <i>Weight</i> | 950 kg | 1030 kg | 1110 kg | 1190 kg |
| <i>Drive</i> | Tractor hydraulic pump with 2 hoses and 2 couplers or PTO 540 rpm | | | |
| <i>Coupling</i> | Automatic 3-point linkage with round bar category N°2 Tractor from 70 HP | | | |
| <i>Electrical drive</i> | 12 Volts Electro-hydraulic controls 12 Volts road lighting kit | | | |



Standard equipment

- Automatic coupling with round bar, category N°2.
- Sign lighting kit.
- Hydraulic offset 1 m.
- 2 hydraulic hoses with 2 ½" male valve couplings.



Adjustable row distance



Air compressor

| | | | £ | Reference |
|---|---|--|---------------|-----------|
| MODELS | | | | |
| BARBED WIRE UNWINDING MACHINE | | | | |
| • CLOTURMATIC 2 RXB : Model 2 rows | | | 11,285 | 77014A |
| • CLOTURMATIC 3 RXB : Model 3 rows | | | 12,990 | 77015A |
| • CLOTURMATIC 4 RXB : Model 4 rows | | | 14,690 | 77016A |
| • CLOTURMATIC 5 RXB : Model 5 rows | | | 16,380 | 77017A |
| OPTIONS | | | | |
| Tilting corrector (tilting +/- 30°) with wireless radio control | Without hydraulic unit | | 2,300 | 77039A |
| | With hydraulic unit (Delivered with oil and shaft) | Without compressor and without air nailing pistol | 4,200 | 77064A |
| | | With Air compressor (PTO drive) : Automatic unwinder for 8 m pipe – Tool chest – Pressure regulator and manometer –50 L air tanks and with air nailing pistol for 11 mm width staples (loading of 130 staples) | 10,455 | 77065A |
| Electro-mechanical time meter (for machine fitted with hydraulic unit - 3-pin socket) | | | 785 | DIV727 |
| Staples | Galvanized - width 11 mm - Length 45 mm - Section 1.7 / 1.9 mm - Packed in a box of 8800 staples | | 310 | 770017 |
| | Stainless steel - Width 11 mm - Length 45 mm - Section 1.7 / 1.9 mm - Packed in a box of 7500 staples | | 1,085 | 770007 |

