



DEROULMATIC 5 PX, with 2 plates equipped with hydraulic winding



DEROULMATIC 5 PX, with 1 hydraulic winding plates



DEROULMATIC 2 PX + irrigation plate + hydraulic winding plate

### Rabaud advantages

- The machine is able to unwind 1 up to 5 plain wire coils in one pass.
- The machine can wind 2 plain wire coils thanks to the option hydraulic winding system to mount on the plate (2 hydraulic winding systems max.).
- Different combinations thanks to removable plates.
- Coil diameter adjustable by support.
- Easy coil extraction thanks to retractable plates and conical supports adjustable according to diameter.

### Technical characteristics

MODEL	DEROULMATIC PX
<i>Coupling</i>	3-point category 1
<i>Dimensions (L x W x H)</i>	1,61 x 0,91 x 1,64 m
<i>Weight</i>	126 kg to 247 kg
<i>Option winding system : Maximum pressure</i>	200 bar
<i>Option winding system : maximum hydraulic flow</i>	50 L/min
<i>Plate for dripping hose</i>	Ø Inner of hose: from 285 mm up to 640 mm Ø Outer maximum of hose: 910 mm Maximum height of hose: 350 mm

### Standard equipment

- 80 mm square tube frame with fixed stands.
- 3-point category 1.
- Coil diameter adjustable by support.



Coils support



Option hydraulic winding system

MODEL	£	Reference
<b>DEROULMATIC PX</b> - Without plate	<b>1,330</b>	77050A
<b>OPTIONS</b>		
Plate for plain wires (max. 5 per DEROULMATIC)	<b>430</b>	77045A
Additional reception platform for irrigation hose hose adaptability (max. 2)	<b>965</b>	77056A
Hydraulic winding set with 2 hoses and 2 ½ male valve couplers <b>to be fitted on the existing plate</b> (2 maximum) - Compatibility for plain wire plate and dripping hose plate	<b>900</b>	77046A
Coils support - 440 mm loading length, maximum 5 coils (250 kg) - One max. by machine	<b>265</b>	77058A
Plate orientation at 75° (not compatible with winding plate lower position)	<b>35</b>	77057A
1-way dual acting hydraulic valve*	<b>485</b>	77054A
2-way dual acting hydraulic valve*	<b>670</b>	77055A

\* Mandatory to control winders from the cabin and/or if tractor equipped with only one single acting valve  
Possibility of adapting stainless steel coils subject to approval by RABAUD (Consult us).