



LOISIR TB 10 EM - Low table



LOISIR TB 10 EM - Low table



LOISIR TB 7 EM - Transport

### Rabaud advantages

- Splitting power : from 7 to 10 Tons.
- Clearance of 0.60 m under wedge, ideal for splitting logs of 0.50 m.
- Electric user's comfort: a simple power socket (single-phase or three-phase).
- Manual double speed of the wedge descent.
- Bimanual control with automatic lifting of the wedge.
- 2 wheels for transportation and easy handling.

### Technical characteristics

MODELS	LOISIR TB 7 EM	LOISIR TB 10 EM	LOISIR TB 10 ET
<i>Hydraulic power</i>	7 Tons	10 Tons	
<i>Splitting capacity / Corner clearance</i>	0,60 m		
<i>2 lowering speeds</i>	<b>Yes : MANU2SPEED</b>		
<i>Length of the wedge</i>	120 mm		
<i>Drive</i>	EM : Single-phase electric motor 2.7 kW / 3.6 HP		ET : Three-phase electric motor 3.75 kW / 5 HP
<i>Minimum amperage</i>	16 A		16 A / 15 A
<i>Transport dimensions (L x W x H)</i>	0,86 x 0,44 x 1,64 m		
<i>Work dimensions (L x W x H)</i>	0,86 x 0,44 x 1,64 m		
<i>Weight</i>	148 kg	150 kg	
<i>Transport</i>	2 wheels - Ø 200 mm		

\* WARNING : electric extension of max. 10 m for SINGLE-PHASE Models.



### Standard equipment

- Wedge made of hard steel cast.
- Large surface platform in grooved metal sheet.
- Bimanual control double speed with automatic adjustable cylinder lift.
- 2 wheels for transport.

DOUBLE SPEED OF THE WEDGE DESCENT

MANU2SPEED : MANUAL MODE



MODELS	£	Reference
<b>LOISIR TB 7</b> (delivered with oil) - <b>Clearance 0.60 m</b> •EM : Single-phase electric motor 220/230 volts (2.7 kW / 3.6 HP)	<b>1,660</b>	70050E
<b>LOISIR TB 10</b> (delivered with oil) - <b>Clearance 0.60 m</b> •EM : Single-phase electric motor 220/230 volts (2.7 kW / 3.6 HP)	<b>1,725</b>	70051E
•ET : Three-phase electric motor 380/400 volts (3,75 kW / 5 HP)	<b>1,835</b>	70052E
<b>OPTIONS</b>		
Swiveling wheel for horizontal movement	<b>40</b>	70055E

