



CLOTURMATIC GRX 8025 PE



CLOTURMATIC GRX 8025 PE



CLOTURMATIC GRX 8025 PE



- Can be fitted to mini-excavators from 6 tons upwards using the quick coupler of your choice.
- Unwinds netting rolls wire from 0 up to 2.50 m height (on GRX 8025) and up to 800 mm diameter.
- Hydraulic wire netting tension system controlled by the operator from the driver's seat.
- Clamp for maintaining tension when fixing or joining rollers.
- Loading platform for putting up the wire netting roll.
- Wire netting always clean and put effortlessly, as the unwinding is made in vertical position.

### Technical characteristics

MODEL	GRX 8025 PE
<i>Wire netting roll diameter</i>	from 0 up to 800 mm
<i>Roll height : without barbed wire</i>	2.50 m max
<i>Dimensions (L x W x H)</i>	1,15 x 0,99 x 2,69 m
<i>Weight</i>	460 kg
<i>Drive</i>	Flow 60 L/min. Pressure 220 bar
<i>Coupling</i>	For mini-excavator minimum 6 Tons

MODEL	£	Reference
<b>CLOTURMATIC GRX 8025 PE</b> Ø roll 800 mm - Maximum height 2,50 m (without coupling hitch)	<b>7,090</b>	77041A
<b>COUPLING HITCH &gt; OBLIGATORY TO DETERMINE</b>		
• Excavator with automatic coupling hitch		See page 210-213
• STANDARD plate 8 holes without bolts for your own adaptation	<b>80</b>	70366703L