



XYLOGRIP 180 R with mini-excavator coupling



XYLOGRIP 230 R



XYLOGRIP 180 R on front loader



### Rabaud advantages

- Two wood grips models adaptable to front loader, telescopic handler, forestry crane, mini-excavator...
- Front loader or telescopic loader attachment with clamp support to prevent tipping during transport - RABAUD Exclusivity.
- 360° rotator in option.
- HLE steel clamps for extra strength.
- Thanks to the large opening of the clamp, you can take several pieces of wood or a bundle of 1 m<sup>3</sup> (1 stère).

### Technical characteristics

MODELS	XYLOGRIP 180	XYLOGRIP 230
<b>Coupling</b>	Excavator from 2.5 to 10 Tons, compact loader, crane, telescopic...	Excavator from 4.5 to 14 Tons, compact loader, crane, telescopic...
<b>Maximum weight</b>	1500 kg	2500 kg
<b>Dimensions of closed clamp (L x W x H)</b>	0,25 x 0,70 x 0,74 m	0,37 x 0,87 x 0,83 m
<b>Maximum opening of the clamp</b>	1,27 m	1,50 m
<b>Clamp surface</b>	0,18 m <sup>2</sup>	0,23 m <sup>2</sup>
<b>Grip weight</b>	Without rotator : 72 kg With rotator : 89 kg	Without rotator : 165 kg With rotator : 194 kg
<b>Working pressure</b>	175 bar	
<b>Clamping force (at end of clamp)</b>	14.2 kN at 200 bar	13.8 kN at 200 bar
<b>Maximum pressure</b>	200 bar	
<b>Oil flow</b>	40 L/min. recommended - 60 L/min. max.	



XYLOGRIP 180  
with direct attachment to mini-excavator



XYLOGRIP 180 R with rotator  
with MORIN quick attachment



XYLOGRIP 180 R  
with telescopic attachment

		£	Reference
<b>MODELS</b>			
<b>XYLOGRIP 180</b> 2 hydraulic hoses without couplers		<b>1,700</b>	78306A
<b>XYLOGRIP 180 R + ROTATOR</b> 4 hydraulic hoses without couplers		<b>2,675</b>	78301A
<b>COUPLING HITCH &gt; OBLIGATORY TO DETERMINE + model to be defined before order</b>			
• Compact loader/Telescopic: suspension and coupling hitch		<b>1,100</b>	78304A
• Mini-excavator / Crane : Coupling hitch	Arm width : 121 to 200 mm	<b>465</b>	73732A
	To screw on quick-fit coupling (reference for quick-fit coupling adaptation to add, see pages 210-213)	<b>535</b>	76904A
• STANDARD plate 8 holes without bolts for your own adaptation		<b>75</b>	70366703L
<b>OPTIONS</b>			
6-way hydraulic valve	+ Electric reel with 15 m cable for charger / telescopic + rotator	<b>1,025</b>	78302A
	+ 12 m extension lead for mini excavator / crane + rotator	<b>745</b>	78303A
Hydraulic rotator (Dynamic rotator load 2000 kg - Torque 75 m/kg at 175 bar) with 2 hydraulic hoses (without coupler)		<b>1,400</b>	78313A
Balance brake		<b>310</b>	26A592
Non-return valve advised for telescopic Merlo, Bobcat, FDI-Sambron		<b>185</b>	78314A

		£	Reference
<b>MODELS</b>			
<b>XYLOGRIP 230</b> 2 hydraulic hoses without couplers		<b>2,430</b>	78338A
<b>XYLOGRIP 230 R + ROTATOR</b> 4 hydraulic hoses without couplers		<b>2,915</b>	78332A
<b>SUSPENSION HITCH &gt; OBLIGATORY TO DETERMINE</b>			
Single shaft		<b>145</b>	26A673
Cardan shaft with balance brake (only with rotator)		<b>310</b>	26A592
<b>COUPLING HITCH &gt; OBLIGATORY TO DETERMINE + model to be defined before order</b>			
• Compact loader/Telescopic: suspension and coupling hitch		<b>1,100</b>	78333A
• Mini-excavator / Crane : Coupling hitch	Arm width : 121 to 200 mm	<b>465</b>	78335A
	To screw on quick-fit coupling (reference for quick-fit coupling adaptation to add, see pages 210-213)	<b>385</b>	76973A
• STANDARD plate 8 holes without bolts for your own adaptation		<b>75</b>	70366703L
<b>OPTIONS</b>			
6-way hydraulic valve	+ Electric reel with 15 m cable for charger / telescopic + rotator	<b>1,025</b>	78302A
	+ 12 m extension lead for mini excavator / crane + rotator	<b>745</b>	78334A
Non-return valve advised for telescopic Merlo, Bobcat, FDI-Sambron		<b>200</b>	78336A

ATTENTION : Provide 2 double-acting lines for the clamp and rotation or 1 DE line + a 12-volt power supply at the end of the jib.



XYLOGRIP 230 R  
with direct attachment to mini-excavator



XYLOGRIP 230 R  
with bolt-on mini-excavator attachment



XYLOGRIP 230 R in transport position  
with telescopic attachment