



F45 HORIZONTAL with transportation axle



F45 HORIZONTAL with forest crane + transportation axle + safety grids



- Horizontal splitting process : power of 45 Tons.
- 4-sided wedge.
- Wedge with height hydraulic adjustment (50 cm range).
- 2,60 m clearance to all diameters and large length logs.
- Large V-shape splitting area.
- Splitting via remote control with automatic cycle.
- Hydraulic power pack with 100 l/min dual-flow pump, 150-litre oil tank with oil and cardan shaft.
- Options : Forestry crane, transportation axle with 2 wheels, electric drive.

Technical characteristics

MODEL	F45 HORIZONTAL
Hydraulic power	45 Tons
Clearance	2,60 m
ø piston / ø rod	150 / 90 mm
Wedge	4-sided wedge with height hydraulic adjustment (50 cm range)
Wedge length	700 mm
Transportation axle version dimensions (L x W x H)	7,24 x 1,99 x 1,75 m
Weight	2680 kg
Drive	PTO 540 rpm, dual pump, flow of 100 L/min. (75 L/min. + 25 L/min.)
Coupling	Towed with axle, dep. 2 wheels 150/55-17

Standard equipment

- Electro-hydraulic control with radio control.
- 4-sided wedge with height hydraulic adjustment.
- Cylinder stroke adjustment.
- Anti-jet sheath on high-pressure hydraulic hoses.



Electric drive option



4-sided wedge with height hydraulic adjustment



Remote radiocontrol

MODEL	£	Reference
F45 HORIZONTAL Clearance 2,60 m - Double pump of 100 l/min (75 l/min + 25 l/min) (Delivered with oil and shaft) Electro-hydraulic control with radio control - 4-sided wedge with height hydraulic adjustment	 Specific conditions : Consult us	35,410 70078E
OPTIONS		
Support stands	Contact us	DIV700
Transportation axle - Width 1.60 m - 2 wheels 150/55-17 - Spiked tyres - Farm coupling ring	2,305	70065B
Safety grids : 2 for the wheels and 1 for the cylinder	1,490	70079E
Forestry crane : XYLOGRUE	See pages 44-45	
Three-phase electric drive 22 kW / 30 HP - 45 A mini.	6,660	70022C