



XYLO-SR 19 with option winch



XYLO-SR 19 CH with hydraulic chain winch



XYLO-SR 17



- Splitting power from 13 to 19 Tons.
- 1.10 m clearance: ideal for 1 m long logs.
- Retractable cylinder. Ideal for the storage (only 2.10 m height with folded cylinder).
- 2 automatic speeds for lowering the wedge.
- Automatic cylinder rising.
- Bimanual control with retaining gripper.
- Log lifter (connected to the wedge with a chain) or hydraulic chain winch.
- Meets the requirements of new European standard EN 609-1 from March 2017.

— Standard equipment

- Retractable cylinder.
- Bimanual control double speed with automatic adjustable cylinder lift.
- Mechanical log-holding system.
- Anti-crushing system.
- Anti-jet sheath on high-pressure hydraulic flexible hoses.

DOUBLE SPEED OF THE WEDGE DESCENT

AUTO2SPEED : AUTOMATIC MODE



Technical characteristics

MODELS	XYLO-SR 13 PH	XYLO-SR 15 CH	XYLO-SR 17 PH	XYLO-SR 19 CH
Hydraulic power	13 Tons	15 Tons	17 Tons	19 Tons
Clearance	1,10 m			
2 lowering speeds	Yes : AUTO2SPEED			
Length of the wedge	170 mm		200 mm	
Work dimensions (L x W x H)	0,90 x 0,95 x 2,65 m	1,25 x 0,95 x 2,65 m	0,95 x 0,95 x 2,65 m	1,30 x 0,95 x 2,65 m
Dimensions with folded cylinder (L x W x H)	0,90 x 0,95 x 2,10 m	1,25 x 0,95 x 2,10 m	0,95 x 0,95 x 2,10 m	1,30 x 0,95 x 2,10 m
Platform dimensions (L x H x W)	0,70 x 0,50 x 0,07 m		0,76 x 0,55 x 0,07 m	
Weight	252 kg 298 kg with winch	357 kg 403 kg with winch	300 kg 346 with winch	405 kg 451 kg with winch
Drive	Tractor pump	PTO 540 rpm, oil flow 33 L/min	Tractor pump	PTO 540 rpm, oil flow 33 L/min
Oil tank	-	30 L	-	30 L
Coupling	Rear 3-point linkage N° 1 & 2			

			£	Reference
MODELS				
XYLO-SR 13 PH : 13 tons	Drive through tractor pump	with log-lifter	2,460	70058E
		winch with ring bolt – 500 kg pulling force - 7 m chain	4,095	70059E
XYLO-SR 15 CH : 15 tons	Drive through PTO 540 rpm	with log-lifter	3,275	70060E
		winch with ring bolt – 500 kg pulling force - 7 m chain	4,835	70061E
XYLO-SR 17 PH : 17 tons	Drive through tractor pump	with log-lifter	2,640	70062E
		winch with ring bolt – 500 kg pulling force - 7 m chain	4,265	70063E
XYLO-SR 19 CH : 19 tons	Drive through PTO 540 rpm	with log-lifter	3,445	70056E
		winch with ring bolt – 500 kg pulling force - 7 m chain	5,010	70057E
OPTIONS				
Log lifter			90	70027E
Hydraulic chain winch, with ring bolt - 500 kg - 7 m chain			1,555	70026E
Self-tightening clamp - Opening 750 mm			215	70035B
Added value ORGANIC oil - Panolin® - for splitters with hydraulic unit - value for 1 L (upon order) / capacity 30 liters			20	22B021



Winch with ring bolt and 7 m chain



Log lifter with to the wedge connected-chain



Bimanual control with retaining gripper

