



SUPERNET 2000 INDUS with option heat engine



SUPERNET 2000 INDUS with option heat engine



SUPERNET 2000 INDUS with option heat engine



- Use for industries (timber, stationery, materials, glass ..), roadways, construction sites...
- Quick mounting on the forklift.
- Possibility to adapt a 5,25 kW / 7 HP heat engine for carriers with low flow.
- Mechanical right/left orientation +/- 20°.
- Polypropylene brush Ø 550 mm with long fibres Ø inner 127 mm / Ø outer 550 mm.
- 3 adjustable depth control wheels.

### Technical characteristics

MODEL	SUPERNET 2000 INDUS.
<i>Brush length</i>	2000 mm
<i>Brush diameter (inner / outer)</i>	127 mm / 550 mm
<i>Brush fibre type</i>	Polypropylene
<i>Orientation</i>	+/- 20°
<i>Dimensions (L x W x H)</i>	1,54 x 2,28 x 0,71 m
<i>Weight</i>	Approx. 180 kg
<i>Coupling</i>	Forklift by 2 sleeves 140 mm wide
<i>Oil flow</i>	15 L/min. mini. - 60 L/min. max.
<i>Maximum pressure</i>	200 bar
<i>Options</i>	Petrol heat engine 5,25 kW/7 HP, Ø 550 mm side brush

### Standard equipment

- Forks.
- Hydraulic hoses with 2 male couplers 1/2.
- Mechanical angling +/- 20°.
- Control wheel.



Tilting setting

	£	Reference
<b>MODEL</b>		
<b>SUPERNET 2000 INDUS.</b> Forks for forklift	<b>2,605</b>	72042G
<b>OPTIONS</b>		
Polyester side brush Ø 550 mm with motor, hoses, 3-way valve	<b>910</b>	72004B
5.25 kW / 7 HP KOHLER petrol engine (3-year warranty) + pump + 10 L oil tank	<b>980</b>	70184A
<b>SPARE BRUSHES</b>		
Side brush Ø 550 mm	<b>125</b>	055A25
Polypropylene brush Ø 550 mm value for 1 m	<b>215</b>	24F002