



MEGANET 3500 on loader



MEGANET 3000



MEGANET 3000

- 3 large sweeping widths: 3 m, 3.50 m or 4.00 m.
- Adaptation on loaders up to 20 Tons or on front 3-point for tractors from 150 HP.
- Robust frame for intensive work
- 2 hydraulic motors with high torque.
- Long fibre polyester brush with reinforced section (inner size: Ø 254 mm / outer size: Ø 800 mm).
- Mechanical orientation (hydraulic in option) +/- 25° to right and left.
- Floating coupling to follow road form thanks to the swiveling system.
- 2 puncture proof depth control wheels, Ø 600 mm, 200 mm wide
- Anti-projection guard adjustable in height.



MEGANET 3000 with collecting box, watering system and specific painting

Technical characteristics

MODELS	MEGANET 3000	MEGANET 3500	MEGANET 4000
Brush length	2880 mm	3480 mm	3900 mm
Diameter (inner / outer)	254 mm / 800 mm		
Hub	Metal without drive shaft bearing		
Brush fibre type	Reinforced polyester		
Angling	Mechanical or hydraulic orientation +/- 25°.		
Dimensions (L x W x H)	2,00 x 3,15 x 1,49 m	2,00 x 3,75 x 1,49 m	2,00 x 4,17 x 1,49 m
Weight	1475 kg	1600 kg	1700 kg
Coupling	Front 3-point hitch N°3 - Loader up to 20 Tons		
Drive	Carrier hydraulic pump		
Hydraulic flow	60 l/min min. - 120 l/min max. (250 l/min on request)		
Pressure	210 bar max.		

Standard equipment

- Polyester brush with reinforced brush Ø 800 mm.
- 2 hydraulic hoses without couplers.
- 2 adjustable depth control wheels, Ø 600 mm, 200 mm wide.
- Mechanical or hydraulic orientation +/- 25°.
- Double anti-projection guard.

	£	Reference	£	Reference	£	Reference
MODELS	MEGANET 3000		MEGANET 3500		MEGANET 4000	
SWEeper with 2 HYDRAULIC motors (for carriers with oil flow > 60 L/min) • With polyester reinforced brush	12,195	72017H	13,835	72018H	16,295	72019H
COUPLING HITCH > OBLIGATORY TO DETERMINE						
• Wheel or track loader up to 20 Tons	1,345	76416A	1,345	76416A	1,345	76416A
• Front 3-point hitch (between 150 and 250 HP)	1,550	72020H	1,550	72020H	1,550	72020H
ANGLING > OBLIGATORY TO DETERMINE						
• Mechanical orientation +/- 25°	910	72049H	910	72049H	910	72049H
• Hydraulic orientation with 2 cylinders +/- 25°	1,010	72029H	1,010	72029H	1,010	72029H
OPTIONS						
Collecting box	6,210	72007J	6,830	72029J	-	-
Anti spatter guard (OBLIGATORY WITHOUT COLLECTING BOX)	730	72018J	775	72031J	-	-
24 V pressure watering with 300 L water tank	1,565	72030J	1,565	72030J	-	-
Spray line kit	on the main brush*	265	72040J	315	72042J	-
	on the collecting box	340	72041J	380	72043J	-
High flow watering with spraying line and firefighter connection (without tank)	500	72032H	500	72032H	500	72032H
LED Lighting with magnetic holders	775	72021H	775	72021H	775	72021H
12V worksite signs kit with retroreflective tape, 2 lumifog... (requires power supply)	485	72047H	485	72047H	485	72047H
Side brush	Contact us		Contact us		Contact us	
6-way hydraulic valve with lead extension 5.00 m long - 24 Volts	695	72048H	695	72048H	695	72048H
Specific painting	165	72009C	165	72009C	165	72009C
EPOXY painting	385	72033G	385	72033G	385	72033G
SPARE BRUSH						
Polyester brush Ø 800 mm, value for 1 m	760	24F018	760	24F018	760	24F018

* 10 sprayers for MEGANET 3000 - 12 sprayers for MEGANET 3500

