



ROBOPEL 250



ROBOPEL 250



ROBOPEL 250



Rabaud advantages

- Semi-automatic peeler adaptable to 3-point tractor. 20 HP combined electric/hydraulic power unit (optional).
- Bark all types of wood: chestnut, acacia, oak... round.
- Peeling of wood from 40 to 250 mm in diameter.
- Wood feed speed can be adjusted: output 60 to 120 piles/h.
- Peeling quality can be adjusted by pressing the two sprockets against the wood.
- Great efficiency thanks to a disc fitted with 6 cutting knives. Knives can be re-sharpened.
- Two V-shaped pneumatic wheels hold the wood in place as it enters and exits the machine.
- Automatic release of drive rollers (optional).
- Chip evacuation blower with 360° swivel chute. Ideal for loading chips onto a trailer.

Technical characteristics

MODEL	ROBOPEL 250
<i>Wood type</i>	For any kind of wood species (special attention to resinous wood), round woods.
<i>Minimum/maximum poste Ø</i>	40 / 250 mm
<i>Number of knives</i>	6
<i>Disc speed</i>	1500 rpm
<i>Work dimensions (L x W x H)</i>	1,99 x 2,39 x 2,67 m
<i>Transport dimensions (L x W x H)</i>	-
<i>Weight</i>	585 kg
<i>Coupling</i>	Tractor 3-point linkage cat. n°2 with removable pins

— Standard equipment —

- Blower for woodchip evacuation with adjustable neck.
- Post support.
- Protection grid.
- Hydraulic set for speed and bark-peeling pressure.



6-knife disc

MODELS	£	Reference
ROBOPEL 250 - Semi-automatic • Disc driven by PTO 540 rpm (delivered with shaft) Hydraulic drive of movements by tractor pump		16,345
75601A		
OPTIONS ROBOPEL 250		
Hydraulic unit, pump 30 L/min, 40 L tank with oil (delivered without shaft)	2,335	70187A
Mixed drive with electro-hydraulic unit 15 kW / 20 HP* and PTO 540 rpm (tractor)	7,260	75607A
Roll post holder	570	75605A
Feet extension 200 mm	235	75617A
Automatic unlocking of intake rollers	1,985	75615A
Automatic unlocking of intake rollers - Mixed drive	3,325	75616A
SPARE PARTS		
ROBOPEL 250 cutting knife (unit price)	100	756015

* 50 A minimum - In case of plugging to power generator, please contact us.