



PROCHAMPION 2500 A With high-flow watering spray line and road sign kit



PROCHAMPION 2500 A With high-flow watering spray line and road sign kit



PROCHAMPION 2500 A with telescopic mixed hitch



Rabaud  
advantages

- Large sweeping widths: 2 m or 2.50 m.a
- Adaptation on front 3-point linkage or on telescopic.
- Robust frame for intensive work
- 1 or 2 hydraulic motor(s) depending on the carrier oil flow (120 L/min. max.).
- Floating coupling to follow road form thanks to the swiveling system
- 30° mechanically swivelling hitch (hydraulic in option).
- +/- 420 mm mechanical offset (hydraulic in option) separate from angling
- Hydraulic engine integrated in the metal hub of the brush to save room and for more protection.
- Wide brush with polyester fibre for better lasting (inner size: Ø 178 mm / outer size: Ø 600 mm).
- 2 height-adjustable, swivelling puncture-proof wheels (Ø 250 mm).
- Pressure watering option to connect directly to your tank.

### Technical characteristics

| MODELS                                | PROCHAMPION 2000 A                           | PROCHAMPION 2500 A   |
|---------------------------------------|--|----------------------|
| <i>Brush length</i>                   | 1980 mm                                      | 2460 mm              |
| <i>Brush diameter (inner / outer)</i> | 178 mm / 600 mm                              |                      |
| <i>Hub</i>                            | Metal  |                      |
| <i>Brush fibre type</i>               | Polyester                                    |                      |
| <i>Offset</i>                         | 420 mm right & left (only on tractor)        |                      |
| <i>Angling</i>                        | +/- 30°                                      |                      |
| <i>Oscillation</i>                    | On floating coupling                         |                      |
| <i>Dimensions (L x W x H)</i>         | 1,67 x 2,09 x 1,26 m                         | 1,67 x 2,55 x 1,26 m |
| <i>Weight (without option)</i>        | 640 kg                                       | 660 kg               |
| <i>Coupling</i>                       | No. 2 front 3-point hitch with removable bar |                      |
| <i>Flow 1 hydraulic motor</i>         | 30 L/min. mini. - 60 L/min. max.             |                      |
| <i>Flow 2 hydraulic motor</i>         | 61 L/min. mini. - 120 L/min. max.            |                      |

### Standard equipment

- Anti-projection guard.
- 3-point linkage with oscillating top link.
- 2 control tyre wheels (diameter 250 mm), swiveling and adjustable in height.
- Brush rings with extra long polyester fibre for longer lifespan.
- Mechanical angling +/- 30°.
- Mechanical offset +/- 420 mm (only on tractor).
- 2 hydraulic hoses with 2 ½" male valve couplings.



PROCHAMPION on tractor front 3-point linkage

|   |  | £   Reference           | £   Reference      |                |
|---|--|-------------------------|--------------------|----------------|
| MODELS  |  | PROCHAMPION 2000 A      | PROCHAMPION 2500 A |                |
| <b>PROCHAMPION for tractor with 1 hydraulic motor (for carrier with oil flow &lt; 60 L/min.)</b><br>• Without hydraulic valves - With polyester brush |  | 7,065   72083E          | 7,455   72082E     |                |
| <b>PROCHAMPION for tractor with 2 hydraulic motor (for carrier with oil flow &gt; 60 L/min.)</b><br>• Without hydraulic valves - With polyester brush |  | 7,730   72085E          | 8,375   72084E     |                |
| OPTIONS   |  |                         |                    |                |
| Hydraulic offset  |  | 785   72032E            | 785   72032E       |                |
| Hydraulic orientation   |  | 865   72086E            | 865   72086E       |                |
| High pressure watering line with 4 sprayers (without water tank)  |  | 405   72064E            | 405   72064E       |                |
| Scrape blade  |  | -                       | 2,910   72061J     |                |
| 12 V worksite signs kit with retroreflective tape, 2 lumifog... (requires power supply)   |  | 340   72095C            | 340   72095C       |                |
| Linkage n°3 with swinging drawbar   |  | 225   72071E            | 225   72071E       |                |
| Mixed hitch for second carrier like a telescopic  |  | 1,060   72064F          | 1,060   72064F     |                |
| 180 bar pressure limiter (for sweeper with only 1 motor)  |  | 220   72022J            | 220   72022J       |                |
| Hydraulic valve   | 6-way valve with electric extension 5 m long | 775   72035G            | 775   72035G       |                |
|   | 8-way valve with electric extension 5 m long | 945   72036G            | 945   72036G       |                |
| Specific painting   |  | 165   72009C            | 165   72009C       |                |
| EPOXY painting  |  | 385   72033G            | 385   72033G       |                |
| Electro-hydraulic control with radio-control  | Sweeper with 1 hydraulic motor               | 2-way valve dual-acting | 2,565   72066E     | 2,565   72066E |
|   |  | 3-way valve dual-acting | 2,970   72067E     | 2,970   72067E |
|   | Sweeper with 2 hydraulic motor               | 2-way valve dual-acting | 3,360   72069E     | 3,360   72069E |
|   |  | 3-way valve dual-acting | 3,685   72070E     | 3,685   72070E |
| SPARE BRUSH   |  |                         |                    |                |
| Polyester brush ring Ø 600 mm, value for 1 m  |  | 420   24F004            | 420   24F004       |                |

### OPTIONS



Linkage n°3 with swinging drawbar



Mixed hitch for second carrier like a telescopic



High pressure watering line, 4 sprayers



Hydraulic angling



Hydraulic offsetting



Scrape blade