



BIFACE 350 with exit conveyor



BIFACE 240 with hydraulic unit



QUADRIFACE 250



Rabaud advantages

- 3 models suitable on tractor 3-point (electric power unit in option).
- Points all sorts of posts (round or split). Mechanical adjustment of the pointing angle (length) and of the final point section.
- Quick pointing (120 to 500 posts per hour) thanks to 2 or 4 blades in high resistance steel depending on models.
- Sharp knives in high-strength steel.
- Automatic release of the knives by the self-supporting pile (on BIFACE 240 and 350) - RABAUD Exclusivity.
- Mechanical adjustment of the pointing angle (length) and of the final point section according to the post diameter
- Safety of the blades supports.



Standard equipment

- Welded frame.
- Post holder.
- 2 or 4 knives in high resistance steel depending on the models.

Technical characteristics

MODELS	BIFACE 240	BIFACE 350	QUADRIFACE 250
Ø Max. post diameter	240 mm	350 mm	250 mm
Knives triggering	Automatic with the post		Electrohydraulic with foot pedal
Pointing	2 sides		4 sides
Drive	Tractor pump 2 couplers or PTO unit 540 rpm. 30 L/min or 3-phase electric 7.5 kW / 10,2 HP	Tractor pump 2 couplers or PTO unit 540 rpm. 30 L/min or 3-phase electric 11 kW / 15 HP	Tractor pump 2 couplers or PTO unit 540 rpm. 35 L/min or 3-phase electric 11 kW / 15 HP
Dimensions without hydraulic unit (L x W x H)	1,91 x 1,12 x 1,28 m	1,35 x 1,87 x 1,63 m	1,33 x 2,11 x 1,33 m
Height with hydraulic unit	1,46 m	1,97 m	1,73 m
Weight without hydraulic unit	330 kg	520 kg	635 kg
Weight with hydraulic unit	415 kg	600 kg	735 kg
Coupling	Tractor 3-point linkage cat. n°2 with removable pins		



Automatic knife release



Mechanical adjustment of the pointing angle and of the final point section



Mechanical adjustment of the pointing angle with 3 settings



Option post counting meter



Electro-hydraulic auxiliary unit on BIFACE 240

				£	Reference
MODELS					
BIFACE 240					
• PH : Tractor pump drive with 2 ½ male valve couplers				5,695	70429A
• CH : PTO 540 rpm drive - Pump 30 L/min. (delivered with oil and shaft)				7,670	70430A
BIFACE 350					
• PH : Tractor pump drive with 2 ½ male valve couplers				7,695	70437A
• CH : PTO 540 rpm drive - Pump 30 L/min (delivered with oil and shaft)				9,105	70438A
• ET : Three-phase electric drive , 11 kW / 15 HP, pump 30 L/min				13,190	70447A
QUADRIFACE 250					
• PH : Tractor pump drive with 2 ½ male valve couplers				10,500	70412A
• CH : PTO 540 rpm drive - Pump 35 L/min (delivered with oil and shaft)				12,440	70421A
OPTIONS					
	BIFACE 240	BIFACE 350	QUADRIFACE 250		
Exit conveyor (2.20 m long – 0.45 m width – Height at 40° : 1.75 m)		●		4,620	70439A
Tool chest		●		260	70440A
Support for chainsaw / hedge trimmer (max. 2)		●		175	71832C
Mechanical and secured post counting meter (6 digits)	●			290	70435A
		●		290	70443A
			●	290	70414A
Time meter	●	●	●	400	26A407
Electromechanical time meter	●	●	●	400	DIV727
Electro-hydraulic auxiliary unit. motor threephase for PH model	7.33 kW / 10 HP - Pump 30 L/min.	●		3,895	70103A
	11 kW / 15 HP - Pump 42 L/min		●	7,800	70129A
Casing kit protection	●			450	70436A
SPARE PARTS					
One spare knife*	●	●		65	704120
One side knife*			●	80	704043
One upper/lower knife*			●	85	704093

* One set for BIFACE 185 = 2 x Ref. 704163

One set for BIFACE 240 = 2 x Ref. 704120

One set for BIFACE 350 = 4 x Ref. 704120

One set for QUADRIFACE 250 = (2 x Ref. 704043) + (2 x Ref. 704093)

The ● means compatibility of options with different models.

The ● indicates compatibility pending approval from RABAUD.

DISCOVER
"MARQUANTS" POST POINTER

CONTACT US

