



SNOWNET 2500



SNOWNET 2500



SNOWNET 2500



Rabaud
advantages

- A range of 3 models : 2 m, 2.50 m or 3 m width.
- Working speed up to 40 km/h.
- Extremely rounded profile with a high density polyethylene protection to easily remove the snow.
- Scraping rubber : thickness 40 mm, Height 250 mm - Hardness 80 Shores.
- Anti-splash flap to avoid snow splashes on signalling (headlights...), casings, engines...
- Hydraulic rotation +/- 28° cylinder with safety relief valve.
- Hitch oscillates +/- 8° to follow road contours.
- Epoxy painting with stainless-steel bolting.
- Lightening kit with LUMIFOG and led lights for a longer life.

Technical characteristics

MODELS	SNOWNET 2000	SNOWNET 2500	SNOWNET 3000
<i>Blade height</i>	0,84 m (0.72 m snow-clearing)		
<i>Snow clearance width at 28°</i>	1,73 m	2,17 m	2,60 m
<i>Oscillation</i>	+/- 8°		
<i>Orientation</i>	+/- 28°		
<i>Dimensions (L x W x H)</i>	1,26 x 2,25 x 1,68 m	1,26 x 2,75 x 1,68 m	1,26 x 3,25 x 1,68 m
<i>Weight (without the tyres) 3-point version</i>	355 kg	395 kg	445 kg
<i>Coupling</i>	3-point front tractor N°2 equipped with floating hitch with 1 DE + R -> 50 HP, telescopic handler and loader		
<i>Power max</i>	150 HP		
<i>Supply</i>	2 hydraulic hoses with 2 ½" male couplers + 1 elec. socket 3-pin		

Standard equipment

- High density polyethylene protection, 10 mm thick with scraping rubber 40 mm thick, 250 mm high, 80 shores hardness and mudguard.
- Signaling kit.
- Hydraulic rotation +/- 28° cylinder with safety relief valve.
- Dual-acting valve plug with 2 hoses, 2 male ½ couplers + 3-pin plug.
- Stand for storage.




Option depth control wheels




Option coupling hitch for other carrier
(telescopic, front loader, ...)




Option coupling hitch for other carrier
(telescopic, front loader, ...)



Snow plough SOWNET 3000



Snow plough SOWNET 2500



Snow plough SOWNET 2000

	£	Reference
MODELS		
SNOWNET 2000 : 2000 mm wide	3,650	71109A
SNOWNET 2500 : 2500 mm wide	3,905	71110A
SNOWNET 3000 : 3000 mm wide	4,385	71111A
COUPLING HITCH > OBLIGATORY TO DETERMINE		
• 3-point front tractor linkage	725	76408A
• Telescopic, Loader	1,190	76409A
• DIN / SETRA plate with a 2nd cylinder for tilting	3,405	76419A
OPTIONS		
2 depth control solid-rubber wheels Ø 25 cm – width 80 mm – greaser – Crank adjusting	825	71105A
Second hydraulic cylinder for tilting	340	71108A
12-volt front light kit - Tractor mounted	550	71106A
Interface linkage for another carrier on SOWNET 3-point hitch – Maximum weight 5 Tons (Telescopic..)	515	76406A
SPARE PARTS		
Snow blade - 40 mm thick - 250 mm High - 80 shore	2,00 m long	255 19B049
	2.50 m long	310 19B046
	3.00 m long	340 19B050

