



SUPERNET 1200 A



SUPERNET 1200 A



- Working width of 1.20 m.
- Brush rings made out of polypropylene with long fibres for long-living brush: inner Ø 127mm / outer Ø 550mm
- Hard-wearing brush thanks to the metal nave
- The height of the brush can be adjusted by means of a spacer to compensate for wear.
- Fixed 20° right-hand orientation.
- Pneumatic control wheel swivels 360°.
- Protected hydraulic motor.
- 2 parking stands.

Technical characteristics

MODEL	SUPERNET 1200 A
<i>Brush length</i>	1200 mm
<i>Diameter (inner / outer)</i>	127 mm / 550 mm
<i>Hub</i>	Metal
<i>Brush fibre type</i>	Polypropylene
<i>Dimensions (L x W x H)</i>	1,36 x 1,40 x 0,87 m
<i>Angling</i>	20° on the right
<i>Weight</i>	105 kg
<i>Coupling</i>	N°0 and 1 3-point hitch with welded studs
<i>Drive</i>	Mini-tractor pump with 2 couplers
<i>Oil flow</i>	15 L/min. mini. - 60 L/min. max.
<i>Oil flow recommended</i>	20 L/min
<i>Pressure</i>	180 bar max.

Standard equipment

- Terrace wheel with pneumatic tyres and height-adjustable spacers.
- Hydraulic motor positioned on the left with 2 hydraulic hoses and 2 ½" male valve couplings.
- Stands for storage.



MODEL	£	Reference
SUPERNET 1200 A With polypropylene brush - Drive by tractor pump - With depth control wheel	2,105	72098D
SPARE BRUSH Polypropylene brush Ø 550 mm value for 1 m	215	24F002