



THE MANUFACTURER'S ADVICE

DEFINE THE POST DRIVER BEST-SUITED FOR YOUR WORKS AND NEEDS

Your carrier	Your activity	Post driving process	Machine	Use	Advantages	Pages
Tractor	Stock breeder, farm contractor, civil engineer, fencing contractor, Agricultural cooperative, etc...	Hammer with halyard	TILTING MAST	Ideal for flat and hilly grounds.	Flat striking	96
			Rotary and pendular TURBOFRAP 200	Ideal for hilly and uneven grounds (serial : automatic plumbing and aligning system, 200° rotation, 3.00 m long posts maximum).	Flat striking Productivity Post driving quality	98
		Vibration with striking head	VIBRESCOPIC II STOCK BREEDER	Ideal for all types of grounds (even very hard). Maximum productivity and safety. Certified for working with only one user.	Safety Productivity Post driving quality	100
			VIBRESCOPIC PRO STOCK BREEDER			
	Wine maker, arborist	Hammer with halyard	Tilting mast VITI	Ideal for flat grounds and low budget.	Flat striking	103
		Vibration with striking head	VIBRESCOPIC II VITI VIBRESCOPIC III VITI VIBRESCOPIC PRO VITI	Ideal for very hard soil, for productivity and safety. Certified for working with only one user.	Safety Productivity Post driving quality	104
VIBRESCOPIC 150	Ideal for small wooden and iron posts (diameter 80mm max. and for activity limited in time).		Price Simple	110		
Grape harvesting machine Straddle tractor Tool carrier	Wine maker, agricultural cooperative, farm contractor	Vibration with striking head	VIBRESCOPIC II on STILTOR PELLENC BRAUD	The only machine customizable and powerful on all these kinds of carriers.	Safety Productivity Post driving quality	108
Mini-excavator and backhoe loader	Farm contractor, civil engineer, fencing contractor	Vibration with striking head	VIBRESCOPIC II PE	The only machine customizable and powerful on all these kinds of carriers.	Safety Productivity Post driving quality	112
On road trailer	Rental agency, CUMA, landscaper	Vibration with striking head	VIBRESCOPIC 15/35 M	New model mounted on a road trailer and driven by an internal combustion engine.	Safety Productivity Post driving quality	111



Post driver TURBOFRAP 200



Vibrating post driver
VIBRESCOPIC STOCK BREEDER



Vibrating post driver
VIBRESCOPIC (straddle tractor)



Vibrating post driver
VIBRESCOPIC II PRO PE



VIBRESCOPIE II BETWEEN WHEELS
+ Pre hole bar driver



VIBRESCOPIE II



VIBRESCOPIE II on mast PROVITIS



Rabaud
advantages

- Drives all posts in all types of grounds thanks to the exclusive power regulation of the striking controlled by the user
- Works in all positions: side shift, tilting and rotation.
- Excellent accuracy: the post is held during the work process.
- Small size during transport and operation (telescopic mast)
- Does not damage posts: power regulation.
- Manual controls by lever or radio remote control, or electro-hydraulic controls.
- Simple use : only one handle for lifting and lowering the hammer and for striking.
- Provides an excellent safety : the hammer vibrates only when the post is in direct contact with the striking head.
- Sturdy, forged, milled and processed striking head, Ø 150 mm (Ø 120 mm optional) – 2 YEARS WARRANTY.

— Standard equipment

- Vibrating hammer.
- Striking head Ø 150 mm.
- Oil filter (except PROVITIS).
- Flow divider 30 L/min.
- Anti-noise headset.

2 YEARS
HAMMER AND STRIKING HEAD WARRANTY

Technical characteristics

MODEL	VIBRESCOPIE on stilt tractor
<i>Maximum post length</i>	Depends on the carrier
<i>Striking head</i>	Ø 150 mm
<i>Percussion hammer</i>	Adjustable from 0 to 950 strokes/min
<i>Hydraulic offset</i>	0.50 m for New Holland Braud - SB series only
<i>Inner/outer mast tilt</i>	20° / 25°



Special assembly : VIBRESCOPIE II STILTOR side shift of 0,75m right – left

		£	Reference
MODELS			
VIBRESCOPIC II SIMPLE VITI BETWEEN TRACTOR WHEELS			
Adaptation between tractor wheels by the customer - without frame but with transversal support and tilting cylinder		11,050	70331C
• 3-way valve with manual control			
• 3-way valve electrohydraulic control		12,965	70332C
OPTIONS			
Hydraulic unit Driven by PTO 540 rpm - Pump 35 L/min. - 40 L tank (with oil and shaft)		Contact us	DIV703
Control Multifunction small joystick (electro-hydraulic version only)		2,180	70377C
Pre-hole bar Ø 55 mm	alone - 1.30 m long	570	70322B
	with hydraulic extraction	manual control	1,885
		electrohydraulic control	1,930
Height extension of the mast for posts of 3.50 m high (to order at purchase)		655	70350C

		£	Reference
MODELS			
VIBRESCOPIC II 15/35 to be adapted on carrier with MULTIPURPOSE MAST			
Hammer travel 500 mm - Pressure limiter 180 bar - 2 hydraulic hoses 1 m long (without couplers) - Storage stand		6,655	70357C
• To adapt on PROVITIS - ATTENTION : delivered without the PROVITIS mast plate			
• To adapt on OTHER CARRIER		Contact us	DIV703

		£	Reference
MODELS			
VIBRESCOPIC II to be adapted on straddle harvester with MULTIPURPOSE ARM			
Pressure limiter 175 bar		9,820	70363C
• For arm PELLENC OPTIMUM (without electric tool recognition), delivered with 2 hydraulic hoses without couplers			
• For arm PELLENC - Mast hydraulic tilting - delivered with 4 hydraulic hoses without coupler		9,815	70327B
• For arm NEW HOLLAND VL and VM series Delivered with 2 hydraulic hoses with New Holland couplers		8,920	70366B
OPTIONS			
Pre-hole bar Ø 55 mm with hydraulic extraction		1,745	70329B

		£	Reference
MODELS			
VIBRESCOPIC II STILTOR to adapt on straddle grape harvester or tool carrier SINGLE-ROWS (for your own adaptation)			
Hammer travel 1100 mm - Hydraulic tilting right/left +/- 20° - Hydraulic tilting front/rear 33°/32° or 44.5/20° Ducted mast with a cylinder - 7 hydraulic hoses and 7 couplers		10,340	70318C
VIBRESCOPIC II STILTOR to adapt on straddle grape harvester or tool carrier 2 ROWS (for your own adaptation)			
Hammer travel 1100 mm - Hydraulic tilting right/left +/- 20° - Hydraulic tilting front/rear 33°/32° or 44.5/20° Ducted mast with a cylinder - 7 hydraulic hoses and 7 couplers		Contact us	
OPTIONS			
3-way valve manual control		845	70387B
3-way valve with electrohydraulic control		Contact us	70389C
Multifunction mini-joystick		Contact us	70388C
Pre-hole bar Ø 30 mm with hydraulic extraction		1,170	70319C

SELECT THE RIGHT COVER HEAD FOR METAL STAKES	
Cover head and support to select	See page 105