



XYLO 13 EM



XYLO 15 ET



XYLO 13 EM - Retractable cylinder



**Rabaud  
advantages**

- Splitting power: 13 or 15 tons.
- Clearance up to 1.10 m, ideal for splitting logs up to 1 m long.
- The convenience of electricity: a single electrical socket (single or three-phase).
- Retractable cylinder. Ideal for storage in a garage (height 1.80 m when cylinder is folded).
- Manual double speed of the wedge descent.
- Bimanual control with automatic lifting of the cylinder. Adjustable cylinder lift.
- 2 wheels for transportation and easy handling.
- Meets the requirements of new European standard EN 609-1 from March 2017.

### Technical characteristics

MODELS	XYLO 13 EM	XYLO 15 ET
<i>Hydraulic power</i>	13 Tons	15 Tons
<i>Splitting capacity / Corner clearance</i>	1,10 m	
<i>2 lowering speeds</i>	<b>Yes : MANU2SPEED</b>	
<i>Length of the wedge</i>	195 mm	
<i>Drive</i>	EM : Single phase electric motor 2,7 kW / 3,6 HP	ET : Three-phase electric motor 3.75 kW / 5 HP
<i>Minimum amperage</i>	16 A	15 A
<i>Transport dimensions (L x W x H)</i>	1,03 x 0,60 x 1,80 m	
<i>Work dimensions (L x W x H)</i>	1,03 x 0,60 x 2,70 m	
<i>Weight</i>	270 kg	
<i>Transport</i>	2 inflatable wheels Ø 260 mm	

\* WARNING : electric extension of max. 10 m for SINGLE-PHASE Models.



### Standard equipment

- Wedge made of hard steel cast.
- Large surface platform in grooved metal sheet.
- Bimanual control double speed with automatic adjustable cylinder lift.
- 2 wheels for transport.

DOUBLE SPEED OF THE WEDGE  
DESCENT

MANU2SPEED : MANUAL MODE



MODELS	£	Reference
<b>XYLO 13 EM</b> (delivered with oil) - <b>Clearance 1.10 m</b> Single-phase electric motor 220/230 volt (2.7 kW / 3.6 HP)	<b>3,225</b>	70012E
<b>XYLO 15 ET</b> (delivered with oil) - <b>Clearance 1.10 m</b> Three-phase electric motor 380/400 volt (3.75 kW / 5 HP)	<b>3,345</b>	70013E