



XYLOCUT 300



XYLOCUT 300



XYLOCUT 300



- Dual function : Combines grappling and cutting functions.
- Adaptable to telescopic handlers.
- 300 mm cutting diameter.
- Cutting branches or undergrowth by hand (a difficult task with a chainsaw).
- Ideal for hardwood.
- Clear cut thanks to the blade mounted on a mobile support.
- Hydraulic tilting : -18° / +85°.
- Lower clamps to hold the wood after cutting and during transport.

Technical characteristics

MODEL	XYLOCUT 300
<i>Coupling</i>	Telescopic
<i>Cutting Ø</i>	300 mm
<i>Knife width</i>	300 mm
<i>Upper grip opening</i>	520 mm
<i>Lower grip opening</i>	450 mm
<i>Cutting power</i>	20 T at 180 bar
<i>Tilting</i>	2 possible cylinder positions -18° up to +66° or from 0° up to 85°
<i>Dimensions (L x W x H)</i>	1,75 x 0,88 x 0,67 m
<i>Weight</i>	504 kg
<i>Oil flow</i>	60 l/min. mini. - 80 l/min. recommended
<i>Main hydraulic pressure</i>	Pressure : 200 bar

Standard equipment

- 2 hydraulic hoses with 2 ½ male valve couplings.
- Knife + counter-knife.

	£	Reference
MODEL		
XYLOCUT 300 - For telescopic - Hydraulic 6-way valve	17,575	78307A
COUPLING HITCH > OBLIGATORY TO DETERMINE + model to be defined before order		
• Telescopic	1,090	78312A
• Mixed linkage for other vehicles	1,135	DIV783
OPTION		
Electric roller with 15 m long electric wire and control button in the cabin with cigarette lighter socket 12 V	760	75143A