




Splitting wedge



XYLOFLAM 200/250 ET with rotary bagging unit for 4 bags



Discharge spout for piled-up bagging with cleaning screener – 20 L bags + receiving table + waste tray

Rabaud advantages

- Designed for scantling, cracked or round timber of all species (soft or hard wood).
- 20 cm max. of length and 25 cm max. of diameter.
- Feeder platform in sturdy steel with an adjustable hydraulic progress.
- Splitting wedge with 5 Tons power.
- 2 types of wood bagging : in bulk with rotative bags unit (4 bags max.) or piled up bagging.
- Possibility of using bags of 20 liters or 40 liters.
- Maximum output (depending on log cross-section): 2.4 m³/h, i.e. 120 x 20-litre bags per hour or 60 x 40-litre bags per hour.
 - In the EM version : output is divided by 30 %.
 - In the INDUS version : output multiplied by 30 %.



Technical characteristics

MODELS	XYLOFLAM 200/250 EM	XYLOFLAM 200/250 ET	XYLOFLAM 200/250 ET INDUS	XYLOFLAM 200/250 PH	XYLOFLAM 200/250 CH	XYLOFLAM 200/250 M
Power	5 Tons					
Max. wood length	200 mm (mini. 160mm)					
Max. wood Ø	Maxi. 250mm					
Wedge	Cross					
Wood cuts	Adjustable from 20 up to 80 mm					
Inlet chute length	1,50 m					
Transport dimensions (L x W x H)	1,34 x 2,15 x 1,85 m					1,26 x 2,15 x 1,85 m
Work dimensions (L x W x H) without bagging system	1,34 x 2,42 x 1,66 m					1,26 x 2,42 x 1,66 m
Weight	555 kg			490 kg	565 kg	545 kg
Drive	Single-phase electric engine 3 kW / 4 HP (EM) three-phase electric engine 5.5 kW / 7.5 HP (ET)			Tractor pump 3-point linkage category N°2 (mini. 25 HP)	PTO 430 rpm, flow 25l/min 3-point linkage category N°2 (mini. 25 HP)	Heat engine KOHLER 7 kW / 9.5 HP (3-year warranty)

Standard equipment

- Filler neck 1,50 m long.
- Feeder platform in steel.
- Crossed splitter with a 5 Tons power.



Filler neck 1,50 m long.



Approx. hourly performance : 2.4 m³
(depending on the sticks' dimensions)

	£	Reference
MODELS		
XYLOFLAM 200/250 EM : Single-phase electric drive - 3 kW / 4 HP* - 17 A	10,810	78620A
XYLOFLAM 200/250 ET : Three-phase electric drive (3 phases + 1 neutral) - 5.5 kW / 7.5 HP *	10,535	78614A
XYLOFLAM 200/250 ET INDUS (boosted version) : Three-phase electric drive (3 phases + 1 neutral) - 5.5 kW / 7.5 HP*	11,520	78634A
XYLOFLAM 200/250 PH : Drive through the tractor's pump with 2 ½ male couplers	9,570	78615A
XYLOFLAM 200/250 CH : Drive through the PTO 430 rpm (delivered with oil and shaft)	10,400	78616A
XYLOFLAM 200/250 M : Powered by KOHLER combustion engine - petrol - 7 kW / 9.5 HP - 3-year warranty Electric start with battery	11,480	78618A
BAGGING SYSTEMS > OBLIGATORY TO DETERMINE		
Rotary bagging unit 4 bags for 20L or 40L bags	535	78619A
Discharge spout for piled-up bagging with cleaning screener Wood maximum length of 200 mm	20 L bag	365
	40 L bag	435
OPTIONS		
Kit support + waste tray for piled-up bagging	245	78612A
Receiving table	310	78613A
Time meter for electric machine	175	78604A
CONSOMMABLES		
20L-mesh bags with zip puller - Dimensions: 40 x 60 cm - (set of 2000 bags)	420	27D122
40L-mesh bags with zip puller - Dimensions: 52 x 80 cm - (set of 1000 bags)	320	27D123

*For any connection to a power generator, please consult technical support beforehand.

BULK bagging :



4-bag rotary unit for bagging wood in bulk.
Possibility of using 20 or 40 litre bags.

PILED-UP bagging :



Bagging of stacked/ranched wood.
Equipped with a waste cleaning grid, waste bin and receiving table for working at the right height. Can be fitted with 20 or 40 litre bags.

NEW XYLOFLAM 330/450+



For more information
CONTACT US

Accepts wood of 15, 20, 25, 30 or 33 cm in length
and max. diameter 450 mm.
Crossed splitter with a 16 Tons power.
Adjustable log cross-section.