



COBRAS



COBRAS



COBRAS



- Only one operator, safe in the tractor, does the maintenance.
- The machine cuts, shreds and sucks up the wastes, which are collected after into a trailer behind the tractor.
- Full safety for the operators working, avoiding them to be on the roads cleaning the cut wastes.
- Very clean cut with no vegetation residue or projections.
- Horizontal or vertical cutting.
- Patented cutting system to replace traditional hedge cutter arm heads.
- Steel disc 400 HB.

Technical characteristics

MODEL	COBRAS 1400
<i>Cutting width</i>	1,40 m
<i>Max. cutting Ø</i>	35 mm
<i>Cutting device</i>	2 opposite drums + 2 reversed discs
<i>Chopping device</i>	Chopper fitted with 5 knives
<i>Cutting height</i>	Depends on the arm mower
<i>Loading</i>	Option : Turbine with a 6 blades rotor
<i>Oil flow</i>	100 L/min
<i>Pressure</i>	300 bar
<i>Weight</i>	420 kg
<i>Tractor power</i>	75 HP mini
<i>Working speed</i>	1,5 km/h to 3 km/h

		£	Reference
MODEL			
COBRAS 1400		16,785	72601A
COUPLING HITCH > OBLIGATORY TO DETERMINE			
• Coupling to determine in accordance with your hitch mower arm (other than NOREMAT)		345	76952A
• On NOREMAT mower arm		830	76961A
OPTIONS			
Deflector	right side	495	72606A
	left side	495	72607A
Holding roller for hedge metal rails		630	72602A
POWER +		2,755	72603A
Simple evacuation tube (hole bar setting)		780	72608A
Hydraulic evacuation tube		1,040	72609A
Articulated, movable evacuation tube		775	72610A
5 m flexible pipe in polypropylene		1,015	72612A
5 m flexible pipe in steel		1,415	72613A
Turbine to be fixed on the trailer - big diameter with 6 removable blades, pipe diameter 250mm, hydraulic drive		6,815	72611A
SELF-ALIGNING turbine - Large diameter with 6 removable blades, pipe diameter 250mm, hydraulic drive		9,070	72604A
Mounting in our own factory on your mowing arm		Contact us	
Specific painting		165	72009C
LOADING TRAILER			
LOADING TRAILER - Capacity 5 Tons		12,090	72605A